

Product: PL2 510

Description: 510g Semi-Coated Banner

Features/Applications:

- White Opaque Substrate for high quality frontlit displays
- Super strong and Durable but has a soft texture and Smooth surface
- For long term use – outdoor banners / signage and indoor display
- Available up to 5m wide

Material Details

Properties	Test Method	Metric
TOTAL WEIGHT	DIN EN ISO 2286-2	510g/m ²
BASE FABRIC	DIN 60001	POLYESTER
YARN	DIN EN ISO 2060	1100 x 1100 dtex
TENSILE STRENGTH	DIN EN ISO 1421	1700x1320 N/5cm
TEAR STRENGTH	DIN 53363	310 x 268 N
ADHESION	DIN53357	NO DELAMINATION
FLAME RESISTANCE	DIN 4102	NFPA 701, B1, M2

Every Surface Covered

Soyang Europe Ltd.

Calder House, Metcalf Drive, Altham, Accrington, Lancashire BB5 5TU UK

Tel: +44(0)161 765 3400 Fax: +44(0)1282 772 982 Web: www.soyang.co.uk



SOYANG
EUROPE

Ink Printability

Solvent	Eco Solvent	UV	Latex
✓	✓	✓	
Screen Printing	Dye Sublimation Transfer	Dye Sublimation Direct	Water Based
✓			

NOTE: technical data corresponds with our latest knowledge and is offered without liability

Every Surface Covered

Soyang Europe Ltd.

Calder House, Metcalf Drive, Altham, Accrington, Lancashire BB5 5TU UK

Tel: +44(0)161 765 3400 Fax: +44(0)1282 772 982 Web: www.soyang.co.uk



SOYANG
EUROPE